

## Products

- CCTV
- Access Control
- ANPR
- Visitor Management
- Panic Alarm Systems
- Interview Recording

## Markets

- Marine
- Oil & Gas
- Law Enforcement
- Parking
- Security



# Explosionproof Bullet Camera - Stainless Steel

FIXED

BHOS4Z4I166

The BHOS-4Z4I-166 Compact camera provides 4x motor-driven optical zoom and delivers 4 MP HD video. The zoom functions can be controlled automatically and precisely from anywhere. In addition, the camera has a wide dynamic range to improve images in challenging lighting conditions.

The camera is housed in a heavy-duty, stainless steel, weatherproof enclosure suitable for hostile environments and is certified for use in hazardous areas. The camera is also available in aluminium. It is ready for mounting, requiring only power and an IP connection. A wall mount arm is provided. Other mounting options are available.

Can be used in Marine and Offshore environments. For example, passenger ships, open bridges, closed spaces, technical rooms - subject to heat generated by equipment, areas where there is a risk of explosion, and visual support for docking manoeuvres.



## Features

- Stainless steel housing
- Weatherproof IP66 for harsh environments
- High resolution 4MP
- 3x motorised zoom lens
- Integrated IR illumination - 50m range
- 12vdc, 24vdc or Poe
- Explosionproof
- Certified for use in hazardous areas
- Pole and corner mounting options

## Products

- CCTV
- Access Control
- ANPR
- Visitor Management
- Panic Alarm Systems
- Interview Recording

## Markets

- Marine
- Oil & Gas
- Law Enforcement
- Parking
- Security

## Technical Specifications

### BHOS4Z4II66


Sensor	1/3" CMOS
Resolution	4MP
Sensitivity	0lx IR
Optical Lens	2.8-12mm x4 30.9-102.8 degrees
IR Illumination range	50m
Wide Dynamic Range	120dB
Image features	Auto Exposure, Auto White Balance, Auto and Manual Iris, Back Light Compensation
Video compression	H264/265/MJPEG
RS485	RJ45
Power supply	12 or 24vdc or PoE 802.3af
Power consumption	8.5W
<b>Impact protection</b>	
Ingress protection	IP66
European/US/EMC	Conforms to UL STD 61010-1 + UL1203 Certified to CSA STD CSA22.2 NO.30 + CAN/CSA C22.2 No. 25 EN 60079-0:2012+A11:203, EN 60079-1:2007, EN 60079-31:2014. ATEX 2014/34/EU
Hazardous Area	Class I, Division 1, Groups B-D, Class II, Division 1, Groups E-G, II 2 GD Ex db IIC T6 Gb, II 2 GD Ex tb IIC T80°C Db IP66
Material	Aluminium
Operating temp	-30 to +60 deg C
Weight (kg)	4.62kg
Dimensions - external (mm)	140H x 140W x 203D
Mounting options	Wall hanging, fixed bracket , pedestal base

## Products

- CCTV
- Access Control
- ANPR
- Visitor Management
- Panic Alarm Systems
- Interview Recording

## Markets

- Marine
- Oil & Gas
- Law Enforcement
- Parking
- Security



**For more information on any of our products  
or services please contact:**

### Paragon Security Limited

Unit 14, Bentalls Business Park, Colchester  
Road, Maldon, Essex CM9 4GD UK  
+44 (0)1245 210914  
[info@paragon-security.com](mailto:info@paragon-security.com)  
[paragon-security.com](http://paragon-security.com)